



Power Hub Rods, Eyenuts and Couplings



Rods with Eyenuts

Features

- Power hub anchor rod and eyenut are assembled at the factory
- Used with solid hub or socket drive power hub screw anchors
- One catalog number for both the rod and eyenut simplifies material handling
- All parts hot dip galvanized

5/8" Diameter

16,000 Lb Ultimate Tensile Strength			
Catalog Number	Length (Ft)	Eyenut Type	Wt Ea (Lb)
D623 1/2 S	3.5	Single Guy Eye	4.6
D623 1/2 D		Double Guy Eye	5.4
D623 1/2 T		Triple Guy Eye	6.0
D62S	7	Single Guy Eye	8.2
D62D		Double Guy Eye	9.1
D62T		Triple Guy Eye	9.4

3/4" Diameter

23,000 Lb Ultimate Tensile Strength			
Catalog Number	Length (Ft)	Eyenut Type	Wt Ea (Lb)
D7531/2S	3.5	Single Guy Eye	6.9
D7531/2D		Double Guy Eye	6.8
D7531/2T		Triple Guy Eye	7.2
D75S	7	Single Guy Eye	11.2
D75D		Double Guy Eye	11.1
D75T		Triple Guy Eye	11.5

1" Diameter

36,000 Lb Ultimate Tensile Strength			
Catalog Number	Length (Ft)	Eyenut Type	Wt Ea (Lb)
D10031/2S	3.5	Single Guy Eye	11.5
D10031/2D		Double Guy Eye	11.4
D10031/2T		Triple Guy Eye	11.8
D100S	7	Single Guy Eye	17.4
D100D		Double Guy Eye	17.4
D100T		Triple Guy Eye	17.7

Rods Only

Features

- Power hub anchor rod used with solid hub or socket drive power hub screw anchors

5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D6231/2	3.5	3.6
D62	7	7.3

3/4" Diameter

23,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D7531/2	3.5	5.0
D75	7	9.3

1" Diameter

36,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D10031/2	3.5	9.6
D100	7	15.5



Rod Extensions with Coupling

Features

- Power hub anchor rod and coupling are assembled at the factory
- Used with solid hub or socket drive power hub screw anchors
- One catalog number for both the rod and coupling simplifies material handling

5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D6231/2C	3.5	4.1
D62C	7	7.7

3/4" Diameter

23,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D7531/2C	3.5	5.5
D75C	7	9.8

1" Diameter

36,000 Lb Ultimate Tensile Strength		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D10031/2C	3.5	10.1
D100C	7	16.0



Eyenuts Only

Features

- Used with power hub rods for solid hub or socket drive power hub screw anchors

5/8" Diameter

16,000 Lb Ultimate Tensile Strength		
Catalog Number	Eyenut Type	Wt Ea (Lb)
D6510A	Single Guy Eye	1.0
D6560A	Double Guy Eye	1.8
D6565	Triple Guy Eye	2.2

3/4" & 1" Diameter

36,000 Lb Ultimate Tensile Strength		
Catalog Number	Eyenut Type	Wt Ea (Lb)
D6512	Single Guy Eye	1.9
D6562A	Double Guy Eye	1.8
D6567	Triple Guy Eye	2.2

Couplings Only

Features

- These couplings are used with all power hub rods when additional rods must be installed

5/8" Diameter

16,000 Lb Ultimate Tensile Strength	
Catalog Number	Wt Ea (Lb)
D352	0.5

3/4" and 1" Diameter

36,000 Lb Ultimate Tensile Strength	
Catalog Number	Wt Ea (Lb)
D354	0.5

