



CATALOG NO.	L	T	ITEM ①	② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪														
				QTY.	QTY.	QTY.	QTY.	QTY.	QTY.	QTY.	QTY.	QTY.	QTY.	QTY.				
J25250.1	7.562	4	25250-A.1	1					1		1	1						
J25250.2	9.062	4	25250-A.2	1				1		1	1							
J25250.6	10.062	6	25250-A.6	1				1		1	1	1						
J25250.7	12.062	6	25250-A.7	1				1		1	1	1						
J25250.34	7.562	4	25250-A.34	1				1		1	1	1			1			
J25250.36	12.062	6	25250-A.36	1				1		1	1	1			1			
J25250.38	10.062	6	25250-A.38	1				1		1	1	1			1			
J25250.40	20.000	8	25250-A.40	1				1		1	1	1			1			
J25250.43	7.062	6	25250-A.43	1				1		1	1	1						
J25250.44	28.000	8	25250-A.44	1				1		1	1	1			1			

NOTES:

- 1) ALL DIMENSIONS ARE REFERENCE AND ARE IN INCHES , EXCEPT AS NOTED
- 2) HOT DIP GALVANIZED (ASTM A-153)
- 4) ADDITIONAL HARDWARE (ITEMS 2 THROUGH 11) TO BE ASSEMBLED WITH THE LINE POST STUD (ITEM 1) AS REQUIRED IN THE TABLE

CUSTOMER DRAWING

CATALOG NO.		
JOSLYN MANUFACTURING CO.		
NO.	REVISION	DATE
UNSPECIFIED FRACTIONAL ±	DIMENSIONAL DECIMAL ±	TOLERANCES ANGULAR ±
3/4" LINE POST STUD ASSEMBLY		DATE 7-20-05
DRAWN JB		DWG. NO. 25250
NO. PROVIDED	SCALE	SHEET 1 of 1