

MPS Catalog Number:

S1 40 80 054 VX SS 011

Date:

09/03/2013

**END FITTINGS**

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

None

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

11 standard

Rod Diameter:

16 mm

Weight Estimate:

9.1 lbs

4.1 kg

**DIMENSIONAL VALUES**

Section Length (L):

65.2 in

1,656 mm

Rubber Length (X):

54 in

1,360 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

6.65 in

169 mm

Dry Arc Distance:

57.2 in

1,453 mm

Leakage Distance:

95 in

2,413 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

559 kV

Min. Withstand:

514 kV

60 Hz Wet Flashover:

495 kV

Min. Withstand:

430 kV

Pos. Critical Impulse Flashover:

949 kV

Min. Withstand:

831 kV

Neg. Critical Impulse Flashover:

1,001 kV

Min. Withstand:

861 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):


25,000 lbs

111.2 kN

Routine Test Load (RTL):

12,500 lbs

55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.