

MPS Catalog Number:  
Date:

S1 40 80 066 MX AL 043  
01/23/2014

**END FITTINGS**

Tower End Fitting: Y-Clevis (Forged Steel)  
Line End Fitting: Ball (Forged Steel) (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower): None  
Corona Ring (Line): None  
Corona Rings are recommended for applications of 230 kV and above  
Number of Sheds: 21 large 22 standard  
Rod Diameter: 16 mm  
Weight Estimate: 12.9 lbs 5.9 kg

**DIMENSIONAL VALUES**


Section Length (L): 78 in 1,981 mm  
Rubber Length (X): 66.4 in 1,687 mm  
Standard Shed Height (P1): 1.5 in 38 mm  
Large Shed Height (P2): 2 in 51 mm  
Projection Ratio (S/P): - 1.5  
Shed Spacing (S): 3 in 76 mm  
Dry Arc Distance: 68.7 in 1,745 mm  
Leakage Distance: 195 in 4,953 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover: 669 kV Min. Withstand: 610 kV  
60 Hz Wet Flashover: 583 kV Min. Withstand: 507 kV  
Pos. Critical Impulse Flashover: 1,124 kV Min. Withstand: 993 kV  
Neg. Critical Impulse Flashover: 1,180 kV Min. Withstand: 1,048 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML): 25,000 lbs 111.2 kN  
Routine Test Load (RTL): 12,500 lbs 55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]  
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.