

MPS Catalog Number:
Date:

S1 40 80 078 MX AL 051
01/23/2014

END FITTINGS

Tower End Fitting: Y-Clevis (Forged Steel)
Line End Fitting: Ball (Forged Steel) (ANSI 52-5)

MATERIAL

Corona Ring (Tower): None
Corona Ring (Line): None
Corona Rings are recommended for applications of 230 kV and above
Number of Sheds: 25 large 26 standard
Rod Diameter: 16 mm
Weight Estimate: 14.6 lbs 6.6 kg

DIMENSIONAL VALUES


Section Length (L): 89.9 in 2,283 mm
Rubber Length (X): 78.3 in 1,989 mm
Standard Shed Height (P1): 1.5 in 38 mm
Large Shed Height (P2): 2 in 51 mm
Projection Ratio (S/P): - 1.5
Shed Spacing (S): 3 in 76 mm
Dry Arc Distance: 80.7 in 2,050 mm
Leakage Distance: 231.6 in 5,883 mm

ELECTRICAL VALUES

60 Hz Dry Flashover: 783 kV Min. Withstand: 707 kV
60 Hz Wet Flashover: 670 kV Min. Withstand: 583 kV
Pos. Critical Impulse Flashover: 1,302 kV Min. Withstand: 1,161 kV
Neg. Critical Impulse Flashover: 1,362 kV Min. Withstand: 1,221 kV

MECHANICAL VALUES

Specified Mech. Load (SML): 25,000 lbs 111.2 kN
Routine Test Load (RTL): 12,500 lbs 55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.