

MPS Catalog Number:

S1 40 80 084 VA SS 041

Date:

09/04/2013

**END FITTINGS**

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

41 standard

Rod Diameter:

16 mm

Weight Estimate:

20.2 lbs

9.2 kg

**DIMENSIONAL VALUES**

Section Length (L):

95.2 in

2,418 mm

Rubber Length (X):

84 in

2,122 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

2.07 in

53 mm

Dry Arc Distance:

83.7 in

2,126 mm

Leakage Distance:

241.4 in

6,132 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

811 kV

Min. Withstand:

732 kV

60 Hz Wet Flashover:

691 kV

Min. Withstand:

601 kV

Pos. Critical Impulse Flashover:

1,347 kV

Min. Withstand:

1,204 kV

Neg. Critical Impulse Flashover:

1,407 kV

Min. Withstand:

1,232 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):


25,000 lbs

111.2 kN

Routine Test Load (RTL):

12,500 lbs

55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.