

MPS Catalog Number:
Date:

S1 70 80 054 MX AL 035
01/23/2014

END FITTINGS

Tower End Fitting: Socket (Forged Steel) (ANSI 52-5)
Line End Fitting: Ball (Forged Steel) (ANSI 52-5)

MATERIAL

Corona Ring (Tower): None
Corona Ring (Line): None
Corona Rings are recommended for applications of 230 kV and above
Number of Sheds: 17 large 18 standard
Rod Diameter: 16 mm
Weight Estimate: 11.5 lbs 5.2 kg

DIMENSIONAL VALUES


Section Length (L): 65 in 1,651 mm
Rubber Length (X): 54.4 in 1,382 mm
Standard Shed Height (P1): 1.5 in 38 mm
Large Shed Height (P2): 2 in 51 mm
Projection Ratio (S/P): - 1.5
Shed Spacing (S): 3 in 76 mm
Dry Arc Distance: 56.7 in 1,440 mm
Leakage Distance: 158.4 in 4,023 mm

ELECTRICAL VALUES

60 Hz Dry Flashover: 554 kV Min. Withstand: 510 kV
60 Hz Wet Flashover: 491 kV Min. Withstand: 427 kV
Pos. Critical Impulse Flashover: 942 kV Min. Withstand: 824 kV
Neg. Critical Impulse Flashover: 994 kV Min. Withstand: 875 kV

MECHANICAL VALUES

Specified Mech. Load (SML): 25,000 lbs 111.2 kN
Routine Test Load (RTL): 12,500 lbs 55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.