

MPS Catalog Number:  
Date:

S1 70 80 072 MX AL 047  
01/23/2014

**END FITTINGS**

Tower End Fitting: Socket (Forged Steel) (ANSI 52-5)  
Line End Fitting: Ball (Forged Steel) (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower): None  
Corona Ring (Line): None  
Corona Rings are recommended for applications of 230 kV and above  
Number of Sheds: 23 large 24 standard  
Rod Diameter: 16 mm  
Weight Estimate: 14 lbs 6.4 kg

**DIMENSIONAL VALUES**


Section Length (L): 83 in 2,108 mm  
Rubber Length (X): 72.4 in 1,839 mm  
Standard Shed Height (P1): 1.5 in 38 mm  
Large Shed Height (P2): 2 in 51 mm  
Projection Ratio (S/P): - 1.5  
Shed Spacing (S): 3 in 76 mm  
Dry Arc Distance: 74.7 in 1,897 mm  
Leakage Distance: 213.3 in 5,418 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover: 726 kV Min. Withstand: 659 kV  
60 Hz Wet Flashover: 627 kV Min. Withstand: 545 kV  
Pos. Critical Impulse Flashover: 1,213 kV Min. Withstand: 1,077 kV  
Neg. Critical Impulse Flashover: 1,272 kV Min. Withstand: 1,134 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML): 25,000 lbs 111.2 kN  
Routine Test Load (RTL): 12,500 lbs 55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]  
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.