

MPS Catalog Number:
Date:

S2 40 80 025 VX SS 014
02/20/2014

END FITTINGS

Tower End Fitting: Y-Clevis
Line End Fitting: Ball (ANSI 52-8/11)

MATERIAL

Corona Ring (Tower): None
Corona Ring (Line): None
Corona Rings are recommended for applications of 230 kV and above
Number of Sheds: 14 standard
Rod Diameter: 24 mm
Weight Estimate: 13 lbs 5.9 kg

DIMENSIONAL VALUES


Section Length (L): 39.6 in 1,006 mm
Rubber Length (X): 25 in 635 mm
Standard Shed Height (P): 2.1 in 54 mm
Shed Spacing (S): 1.8 in 46 mm
Dry Arc Distance: 28.7 in 729 mm
Leakage Distance: 78.1 in 1,984 mm

ELECTRICAL VALUES

60 Hz Dry Flashover: 288 kV Min. Withstand: 268 kV
60 Hz Wet Flashover: 260 kV Min. Withstand: 226 kV
Pos. Critical Impulse Flashover: 500 kV Min. Withstand: 430 kV
Neg. Critical Impulse Flashover: 535 kV Min. Withstand: 461 kV

MECHANICAL VALUES

Specified Mech. Load (SML): 50,000 lbs 222.4 kN
Routine Test Load (RTL): 25,000 lbs 111.2 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.