

MPS Catalog Number:
Date:

S2 40 80 037 VX SS 023
02/20/2014

END FITTINGS

Tower End Fitting: Y-Clevis
Line End Fitting: Ball (ANSI 52-8/11)

MATERIAL

Corona Ring (Tower): None
Corona Ring (Line): None
Corona Rings are recommended for applications of 230 kV and above
Number of Sheds: 23 standard
Rod Diameter: 24 mm
Weight Estimate: 16.7 lbs 7.6 kg

DIMENSIONAL VALUES


Section Length (L): 51.6 in 1,311 mm
Rubber Length (X): 37 in 940 mm
Standard Shed Height (P): 2.1 in 54 mm
Shed Spacing (S): 1.58 in 40 mm
Dry Arc Distance: 40.7 in 1,034 mm
Leakage Distance: 125 in 3,175 mm

ELECTRICAL VALUES

60 Hz Dry Flashover: 402 kV Min. Withstand: 373 kV
60 Hz Wet Flashover: 362 kV Min. Withstand: 315 kV
Pos. Critical Impulse Flashover: 693 kV Min. Withstand: 599 kV
Neg. Critical Impulse Flashover: 736 kV Min. Withstand: 629 kV

MECHANICAL VALUES

Specified Mech. Load (SML): 50,000 lbs 222.4 kN
Routine Test Load (RTL): 25,000 lbs 111.2 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.