

MPS Catalog Number:

S2 40 80 070 VA SS 028

Date:

02/24/2014

END FITTINGS

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-8/11)

MATERIAL

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

28 standard

Rod Diameter:

24 mm

Weight Estimate:

22.8 lbs

10.3 kg

DIMENSIONAL VALUES

Section Length (L):

84.6 in

2,149 mm

Rubber Length (X):

70 in

1,778 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

2.63 in

67 mm

Dry Arc Distance:

70.2 in

1,783 mm

Leakage Distance:

177.4 in

4,506 mm

ELECTRICAL VALUES

60 Hz Dry Flashover:

683 kV

Min. Withstand:

622 kV

60 Hz Wet Flashover:

594 kV

Min. Withstand:

516 kV

Pos. Critical Impulse Flashover:

1,146 kV

Min. Withstand:

1,014 kV

Neg. Critical Impulse Flashover:

1,203 kV

Min. Withstand:

1,043 kV

MECHANICAL VALUES

Specified Mech. Load (SML):


50,000 lbs

222.4 kN

Routine Test Load (RTL):

25,000 lbs

111.2 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.