

MPS Catalog Number:

S5 40 80 025 VX SS 015

Date:

09/05/2013

END FITTINGS

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

MATERIAL

Corona Ring (Tower):

None

Corona Ring (Line):

None

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

15 standard

Rod Diameter:

16 mm

Weight Estimate:

13.9 lbs

6.3 kg

DIMENSIONAL VALUES

Section Length (L):

36.2 in

919 mm

Rubber Length (X):

25 in

624 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

1.6 in

41 mm

Dry Arc Distance:

28.2 in

716 mm

Leakage Distance:

81.5 in

2,070 mm

ELECTRICAL VALUES

60 Hz Dry Flashover:

283 kV

Min. Withstand:

264 kV

60 Hz Wet Flashover:

255 kV

Min. Withstand:

222 kV

Pos. Critical Impulse Flashover:

491 kV

Min. Withstand:

423 kV

Neg. Critical Impulse Flashover:

527 kV

Min. Withstand:

454 kV

MECHANICAL VALUES

Specified Mech. Load (SML):


30,000 lbs

133.4 kN

Routine Test Load (RTL):

15,000 lbs

66.7 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.