

MPS Catalog Number:

S5 40 80 036 VX SS 016

Date:

09/05/2013

**END FITTINGS**

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

None

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

16 standard

Rod Diameter:

16 mm

Weight Estimate:

14.6 lbs

6.6 kg

**DIMENSIONAL VALUES**

Section Length (L):

47.2 in

1,199 mm

Rubber Length (X):

36 in

903 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

2.38 in

60 mm

Dry Arc Distance:

39.2 in

996 mm

Leakage Distance:

96.4 in

2,449 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

388 kV

Min. Withstand:

360 kV

60 Hz Wet Flashover:

349 kV

Min. Withstand:

304 kV

Pos. Critical Impulse Flashover:

669 kV

Min. Withstand:

577 kV

Neg. Critical Impulse Flashover:

712 kV

Min. Withstand:

608 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):


30,000 lbs

133.4 kN

Routine Test Load (RTL):

15,000 lbs

66.7 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.