

MPS Catalog Number:

S5 40 80 054 VX SS 011

Date:

09/05/2013

**END FITTINGS**

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

None

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

11 standard

Rod Diameter:

16 mm

Weight Estimate:

14 lbs

6.4 kg

**DIMENSIONAL VALUES**

Section Length (L):

65.2 in 1,656 mm

Rubber Length (X):

54 in 1,360 mm

Standard Shed Height (P):

2.1 in 54 mm

Shed Spacing (S):

6.65 in 169 mm

Dry Arc Distance:

57.2 in 1,453 mm

Leakage Distance:

95 in 2,413 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

559 kV

Min. Withstand:

514 kV

60 Hz Wet Flashover:

495 kV

Min. Withstand:

430 kV

Pos. Critical Impulse Flashover:

949 kV

Min. Withstand:

831 kV

Neg. Critical Impulse Flashover:

1,001 kV

Min. Withstand:

861 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):

30,000 lbs

133.4 kN

Routine Test Load (RTL):

15,000 lbs

66.7 kN

