

MPS Catalog Number:

S5 40 80 066 VA SS 032

Date:

09/05/2013

END FITTINGS

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

MATERIAL

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

32 standard

Rod Diameter:

16 mm

Weight Estimate:

17.2 lbs

7.8 kg

DIMENSIONAL VALUES

Section Length (L):

77.2 in

1,961 mm

Rubber Length (X):

66 in

1,665 mm

Standard Shed Height (P):

2.1 in

54 mm

Shed Spacing (S):

2.09 in

53 mm

Dry Arc Distance:

65.7 in

1,669 mm

Leakage Distance:

188.5 in

4,788 mm

ELECTRICAL VALUES

60 Hz Dry Flashover:

640 kV

Min. Withstand:

585 kV

60 Hz Wet Flashover:

560 kV

Min. Withstand:

487 kV

Pos. Critical Impulse Flashover:

1,078 kV

Min. Withstand:

950 kV

Neg. Critical Impulse Flashover:

1,134 kV

Min. Withstand:

980 kV

MECHANICAL VALUES

Specified Mech. Load (SML):


30,000 lbs

133.4 kN

Routine Test Load (RTL):

15,000 lbs

66.7 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.