

MPS Catalog Number:
Date:

S5 40 80 114 VB SS 030
09/05/2013

END FITTINGS

Tower End Fitting: Y-Clevis
Line End Fitting: Ball (ANSI 52-5)

MATERIAL

Corona Ring (Tower): None
Corona Ring (Line): 12" Corona Ring
Corona Rings are recommended for applications of 230 kV and above
Number of Sheds: 30 standard
Rod Diameter: 16 mm
Weight Estimate: 21.3 lbs 9.7 kg

DIMENSIONAL VALUES


Section Length (L): 125.2 in 3,180 mm
Rubber Length (X): 114 in 2,884 mm
Standard Shed Height (P): 2.1 in 54 mm
Shed Spacing (S): 4.1 in 104 mm
Dry Arc Distance: 113.7 in 2,888 mm
Leakage Distance: 228.7 in 5,809 mm

ELECTRICAL VALUES

60 Hz Dry Flashover: 1,067 kV Min. Withstand: 966 kV
60 Hz Wet Flashover: 920 kV Min. Withstand: 768 kV
Pos. Critical Impulse Flashover: 1,784 kV Min. Withstand: 1,603 kV
Neg. Critical Impulse Flashover: 1,850 kV Min. Withstand: 1,667 kV

MECHANICAL VALUES

Specified Mech. Load (SML): 30,000 lbs 133.4 kN
Routine Test Load (RTL): 15,000 lbs 66.7 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.