

MPS Catalog Number:  
Date:

S6 40 82 052 VX SS 026  
02/27/2014

**END FITTINGS**

Tower End Fitting: Y-Clevis  
Line End Fitting: Ball (ANSI 52-8)

**MATERIAL**

Corona Ring (Tower): None  
Corona Ring (Line): None  
Corona Rings are recommended for applications of 230 kV and above  
Number of Sheds: 26 standard  
Rod Diameter: 18 mm  
Weight Estimate: 19 lbs 8.6 kg

**DIMENSIONAL VALUES**


Section Length (L): 65.4 in 1,661 mm  
Rubber Length (X): 52 in 1,321 mm  
Standard Shed Height (P): 2.2 in 55 mm  
Shed Spacing (S): 2.05 in 52 mm  
Dry Arc Distance: 55.7 in 1,415 mm  
Leakage Distance: 151.6 in 3,851 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover: 545 kV Min. Withstand: 501 kV  
60 Hz Wet Flashover: 483 kV Min. Withstand: 420 kV  
Pos. Critical Impulse Flashover: 926 kV Min. Withstand: 810 kV  
Neg. Critical Impulse Flashover: 978 kV Min. Withstand: 840 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML): 36,000 lbs 160.1 kN  
Routine Test Load (RTL): 18,000 lbs 80.1 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]  
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.