

MPS Catalog Number:

S6 40 82 091 VA SS 029

Date:

02/28/2014

**END FITTINGS**

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-8)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

29 standard

Rod Diameter:

18 mm

Weight Estimate:

18.9 lbs

8.6 kg

**DIMENSIONAL VALUES**

Section Length (L):

104.4 in

2,652 mm

Rubber Length (X):

91 in

2,311 mm

Standard Shed Height (P):

2.2 in

55 mm

Shed Spacing (S):

3.36 in

85 mm

Dry Arc Distance:

91.2 in

2,316 mm

Leakage Distance:

202.3 in

5,138 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

883 kV

Min. Withstand:

791 kV

60 Hz Wet Flashover:

753 kV

Min. Withstand:

646 kV

Pos. Critical Impulse Flashover:

1,457 kV

Min. Withstand:

1,309 kV

Neg. Critical Impulse Flashover:

1,519 kV

Min. Withstand:

1,338 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):


36,000 lbs

160.1 kN

Routine Test Load (RTL):

18,000 lbs

80.1 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.